



- 1 The non-linear PDE

$$u_t + uu_x = 0$$

is commonly known as *Burgers' equation*. It can be seen as a differential form of a conservation law with flux density $j(u) = \frac{1}{2}u^2$ and production rate $q = 0$.

- (a) Compute solutions of Burgers' equation for the initial conditions

$$u_0(x) = \begin{cases} 0 & \text{if } x < 0, \\ 1 & \text{if } x > 0, \end{cases}$$

and

$$u_0(x) = \begin{cases} 1 & \text{if } x < 0, \\ 0 & \text{if } x > 0. \end{cases}$$

- (b) We now consider the non-homogeneous Burgers equation with right hand side (“production term”) $-u$, that is,

$$u_t + uu_x = -u.$$

Compute the solutions of this equation with initial condition

$$u(x, t) = \begin{cases} 0 & \text{if } x < 0, \\ x & \text{if } x > 0. \end{cases}$$

- 2 Use the method of characteristics to solve these initial value problems for $t > 0$.

(a) $u_t + u_x = -u, \quad u(x, 0) = u_0(x)$

(b) $u_t + u_x = x, \quad u(x, 0) = u_0(x)$

- 3 (Problem 1.13 in Ockendon, Howison, Lacey, Movchan, Applied Partial Differential Equations)

Paint flowing down a wall has thickness $u(x, t)$ satisfying $\frac{\partial u}{\partial t} + u^2 \frac{\partial u}{\partial x} = 0$ for $t > 0$.

- (a) Show that the characteristics are straight and that the Rankine–Hugoniot condition at a shock $x = S(t)$ is $dS/dt = [\frac{1}{3}u^3]_-^+ / [u]_-^+$.

A stripe of paint is applied at $t = 0$ so that

$$u(x, 0) = \begin{cases} 0, & x < 0 \text{ or } x > 1, \\ 1, & 0 < x < 1. \end{cases}$$

(b) Show that, for small enough t ,

$$u = \begin{cases} 0, & x < 0, \\ (x/t)^{1/2}, & 0 < x < t, \\ 1, & t < x < S(t), \\ 0, & S(t) < x, \end{cases}$$

where the shock is given by $x = S(t) = 1 + t/3$.

(c) Explain why this solution changes at $t = 3/2$, and show that thereafter

$$\frac{dS}{dt} = \frac{S}{3t}.$$

4 (Exercise 7.2.2 p. 73 in Krogstad)

A groundwater reservoir R , consists of porous sandstone filled with water. The pores constitute a constant fraction Φ of the volume ($0 < \Phi < 1$). The boundary to R , ∂R , is partially open so that water can flow in and out. Two wells are drilled in the reservoir.

(a) Set up a conservation law in the integral form of the water in the reservoir, where the flux $\mathbf{j}(\mathbf{x}, t)$ is not yet specified. What is the expression if the density of water ρ and all the properties of R are constant?

To find an expression for the flux of water [$\text{m}^3/(\text{m}^2 \cdot \text{s})$], we assume that it only depends on viscosity μ [$\text{kg}/(\text{m} \cdot \text{s})$], the fluid resistance in the rock (permeability K [m^2]), and the pressure gradient ∇p . (Here and in the rest of the exercise, we assume that ρ is constant, so that we measure the water flow in volume.)

(b) Show by using dimensional analysis that

$$\mathbf{j} = -k \frac{K}{\mu} \nabla p,$$

where k is a dimensionless constant (the sign is physically reasonable).

To study how oil pollution in the reservoir will spread, we look at a rod-shaped rock sample, which in addition to water also contains oil. All the pores are either filled with water or oil, and a rock volume V will contain a volume $S_o \Phi V$ of oil and $S_v \Phi V$ of water, where $S_o + S_v = 1$. We assume that water and oil have the same pressure and that the flux (in the x -direction along the rod) can be written in the form

$$j_i = -k_i (S_i) \frac{K}{\mu_i} \frac{\partial p}{\partial x}, \quad i = o, v.$$

(c) Specify the conservation laws for oil and water for the section of the rod between $x = a$ and $x = b$, and show that if the pressure gradient is

$$q = j_o + j_v = \text{constant},$$

then, when $S \equiv S_v$, we get the hyperbolic equation

$$\Phi \frac{\partial S}{\partial t} + \frac{\partial}{\partial x} f(S) = 0,$$

$$(1) \quad f(S) = \frac{q k_v(S) / \mu_v}{k_o(1-S) / \mu_o + k_v(S) / \mu_v}.$$

- (d) Let $\mu_o = \mu_v$ and $k_o(1 - S) = 1 - S^2$, $k_v(S) = S^2$. Solve (1) for $t > 0$ for a rod with length L when

$$\begin{aligned}S(x, 0) &= 1 - x/L, & 0 \leq x \leq L, \\S(0, t) &= 1, & 0 \leq t.\end{aligned}$$