WEEK 16, 2006 April 20 and 21

# TMA4275 LIFETIME ANALYSIS

Bo Lindqvist


Department of Mathematical Sciences

NTNU

bo@math.ntnu.no http://www.math.ntnu.no/~bo/

1

Cumulative Number of Unscheduled Maintenance Actions Versus Operating Hours with Power and Loglinear NHPP Models for a USS Grampus Diesel Engine



# Results of Fitting NHPP Models to the USS Grampus Diesel Engine Data

- Both models seem to fit the data very well.
- For the power recurrence rate model,  $\hat{\beta}$ =1.22 and  $\hat{\eta}$  =0.553.
- For the loglinear recurrence rate model,  $\hat{\gamma}_0 = 1.01$  and  $\hat{\gamma}_1 = .0377$ .
- Times between recurrences are consistent with a HPP:
  - ▶ the Lewis-Robinson test gave  $Z_{LR} = 1.02$  with p-value p = .21.
  - ▶ the MIL-HDBk-189 test gave  $X_{\text{MHB}}^2 = 92$  with p-value p = .08.

3



Minitab provides five trend tests for data with multiple systems: MIL-hdbk-189 (TTT-based), MIL-hdbk-189 (Pooled), Laplace's (TTT-based), Laplace's (Pooled), and Anderson-Darling. The pooled Laplace and military handbook tests reduce to their respective TTT-based tests when there is only one system. These tests behave differently under the following two circumstances:

- 1 the data follow a non-monotonic trend
- 2 the data are from heterogeneous systems

#### Monotonic and non-monotonic trends

There is a trend in the pattern of times between failure if the times change in a systematic way. Trends can be:

- . monotonic times between failures are getting either consistently longer (decreasing trend) or consistently shorter (increasing trend)
- . non-monotonic times between failures alternate between increasing and decreasing trend (cyclic) or have a decreasing trend, no trend, and then increasing trend (bathtub)

The Anderson-Darling test will reject the null hypothesis in the presence of both monotonic and non-monotonic trends. The other tests will generally only detect monotonic trends. While the Anderson-Darling test is useful if you suspect the existence of a cyclic or other non-monotonic trend, the other tests are more powerful in the case of a monotonic trend.

#### Homogeneous and heterogeneous systems

The null hypothesis of no trend differs slightly for the different tests:

- The null hypothesis for the pooled tests (MIL-hdbk-189 and Laplace's) is that the data come from a homogeneous Poisson processes (HPP) with a possibly different MTBF for each system. Thus, rejecting the null hypothesis means that you can definitely conclude there is a trend in your data.
- The null hypothesis for the TTT-based tests (MIL-hdbk-189, Laplace's, and Anderson-Darling) is that the data come from a homogeneous Posson process (HPP) with the same MTBF for each system. Thus, rejecting the null hypothesis could mean that either there is a trend in your data or your data come from heterogeneous systems. Therefore, you should use TTT-based tests only when you are confident that your systems are homogeneous.

The table below summarizes the different null hypotheses associated with the trend tests.

20	MIL-hdbk-189 (Pooled)	MIL-hdbk-189 (TTT-based)	Laplace's (Pooled)	Laplace's (TTT-based)	Anderson- Darling
Null Hypothesis	HPP (possibly different MTBFs)	HPP (equal MTBFs)	HPP (possibly different MTBFs	HPP (equal )MTBFs)	HPP (possibly different MTBFs)
Rejecting H <sub>0</sub> means	monotonic trend	monotonic trend or systems are heterogeneous	monotonic trend	or systems are	monotonic trend or non- monotonic trend or systems are heterogeneous

See 12 for more information concerning these tests.



# TTT-based tests for trend in repairable systems data

#### Jan Terje Kvaløy & Bo Henry Lindqvist


Department of Mathematical Sciences, Norwegian University of Science and Technology, N-7034 Trondheim, Norway

(Received 25 September 1996; revised 24 January 1997; accepted 15 July 1997)


A major aspect of analysis of failure data for repairable systems is the testing for a possible trend in interfailure times. This paper reviews some important and popular graphical methods and tests for the nonhomogeneous Poisson process model. In particular, the total time on test (TTT) plot is considered, and trend tests based on the TTT-statistic are motivated and derived. In particular, a test based on the Anderson–Darling statistic is suggested. The tests are evaluated and compared in a simulation study, both with respect to the achievement of correct significance level and rejection power. The considered alternatives to 'no trend' are the log-linear, power law and a class of bathtub-shaped intensity functions. The simulation study involves single systems, as well as the case where several independent systems of the same kind are observed. © 1998 Elsevier Science Limited.

5

#### Valveseat Data



### Valveseat Data



7

## Valveseat Data

#### Trend Tests

	MIL-Hdbk-189		Laplace's		
	TTT-based	Pooled	TTT-based	Pooled	Anderson-Darling
Test Statistic	80,28	66,15	0,46	2,38	0,80
P-Value	0,249	0,017	0,645	0,017	0,478
DE	96	96			